



TINT FOR ALIPOLY 85

Product Information

Category: Sealer Product No.

2500-AP85-TINT

32 oz for 2-gal kit

Description and Use:

Conveniently designed for “on the jobsite” tinting. Mixes easily with freshly mixed kit of Alipoly 85. May be also used for CRU-75.

Engineered to conceal MVR9 MVEP epoxies as those products are subject to UV fade and the tinted Alipoly with its UV inhibitors conceal and resist color fade.

Should be used as a base for partial broadcast of chips coat or no chips broadcast to replacement epoxy as the base coat. Tinted Alipoly with partial or no broadcast of chips is UV resistant and excellent for clear coat of Alipoly gloss or satin.

This is NOT to be used for mixing with any of our epoxy products or other sealers.

Colors:

- Light Grey
- Dark Grey
- Tile Red
- Tan
- Beige
- Safety Blue
- White
- Black
- Safety Yellow

Coverage:

Note: The addition of this tint will increase the kit square foot coverage by as much as 15%.

Packaging:

Approximately 32 oz.

Mixing:

Premix part A and shake part B before adding this tint. Then pour entire contents of tint.

Spin for up to 1 minute using a drill mixer at slower rate of 300rpm until product is thoroughly mixed. Scrape sides of mixing bucket to help assure thorough mixing. Material cannot be properly mixed by hand even in small batches.

Thinning:

Thinning is **not** suggested.

Application:

Follow application instructions for Alipoly 85.

Handling Precautions:

Refer to SDS before using it.

Clean Up:

Acetone will help remove un-cured material off tools, but once it is cured it will need to be removed mechanically.

Wear Personal Protective Equipment. Read SDS before using this product.
DOT/Flash Point – Non-flammable Liquid Classification, not regulated.

Manufacturer/Distributor Warranty: As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer's and consumer's use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.

