



Acrylic Chips
Product Information
Category: Color Medium
55 lb boxes
6500 Series

Description and Use:

Acrylic chips are manufactured for use in the following application:

- | | |
|---|--|
| <input type="checkbox"/> Floor Overlays / Micro-Topping | <input type="checkbox"/> 3D |
| <input type="checkbox"/> Interior | <input checked="" type="checkbox"/> Epoxy Flooring |
| <input type="checkbox"/> Exterior | <input type="checkbox"/> Shower FX |
| <input type="checkbox"/> Countertop | <input type="checkbox"/> Outdoor Islands |

Color:

Available in 1/4" with unlimited and standard choice. Refer to epoxy chip color chart.

Package Size:

55lb boxes

Uses:

Broadcasted in Granicrete floor epoxies while epoxies are wet.
Application rate for partial broadcast is 1lb per 100 square feet.
Application rate for bull broadcast is 1lb per 8-10 square feet.

Acrylic chips should be sealed with Granicrete performance sealers.
Follow further directions in Granicrete's Epoxy & Real MetalliX Flooring Manual

Wear Personal Protective Equipment.
Read SDS before using this product.
DOT not regulated.

Manufacturer/Distributor Warranty: As neither the manufacturer nor the distributor has control over the actual installation of this product, the manufacturer and distributor disclaim any and all warranties expressed or implied regarding color shade, appearance, and product performance at and after opening product containers. Manufacturer and distributor recommendations and suggestions are made without guarantee. Conditions of installer's and consumer's use of this product are beyond the control of manufacturer and distributor. Manufacturer and distributor disclaim any liability incurred in connection with the use of this product or information contained herein.